

Test Started: 10/21/2005 3:12 pm Test Site: Finished Basement Avg.: 69.0 29.9 51
 Test Ended: 10/25/2005 2:14 pm Test Duration: 95 hours Max.: 73.0 30.0 76

AVERAGE RADON CONCENTRATION: 71.5 pCi/l

Test met minimum EPA sampling duration.

Time	10/21/2005		10/22/2005		10/23/2005		10/24/2005		10/25/2005	
	pCi/l	Flags	pCi/l	Flags	pCi/l	Flags	pCi/l	Flags	pCi/l	Flags
00:12 am			86.6		64.8		81.1		67.4	
01:12			94.8		68.2		81.5		67.7	
02:12			100		71.9		81.0		66.2	
03:12			102		74.5		79.8		64.9	
04:12			103		75.9		77.4		63.9	
05:12			103		76.0		74.7		64.9	
06:12			101		74.0		71.7		65.7	
07:12			99.8		71.5		68.6		66.5	
08:12			98.6		67.6		66.3		66.7	
09:12			97.6		63.8		64.5		66.9	
10:12			96.6		59.2		63.3		67.1	
11:12			94.8		56.6		61.5		66.2	
12:12 pm			91.4		54.8		59.8		66.2	
01:12			87.5		54.6		58.4		66.8	
02:12			83.5		53.7		58.0		67.9	
03:12			80.2		53.1		58.8			
04:12	Eq.		77.0		53.2		59.9			
05:12	Eq.		74.1		55.4		61.4			
06:12	Eq.		71.0		60.9		62.1			
07:12	Eq.		67.6		67.1		64.0			
08:12			53.1		73.6		65.0			
09:12			56.6		77.1		65.9			
10:12			64.8		79.5		65.8			
11:12			75.6		80.3		66.6			

Flags: P=AC Power Disruption, T=Tilt
 Eq. = Equalization Period

While every effort was made to maintain optimum quality control and EPA Protocol during the testing period, neither Radalink, Inc. or its licensed agents provide any warranty, expressed or implied, for the consequences of erroneous test results. There can be some uncertainty with any measurement due to statistical variations, extreme weather changes, operation of the building, and other factors, Radalink, Inc. and its licensed operators shall not be liable under any charge or claim for losses, claims, charges,