

## Performance Data @ ARI Standard Conditions—Cooling (Con't.)

Model Numbers		80°F [26.5°C] DB/67°F [19.5°C] WB Indoor Air 95°F [35°C] DB Outdoor Air					Sound Rating	Indoor CFM [L/s]
Outdoor Unit RAKB-	Indoor Coil and/or Air Handler	Total Capacity BTU/H [kW]	Net Sensible BTU/H [kW]	Net Latent BTU/H [kW]	EER	SEER		
060CA/DA/JA/YA	RCBA-6089 ①	56,000 [16.4]	43,100 [12.6]	12,900 [3.8]	9.5	10.0	8.2	2000 [944]
	RCBA-6089+RXMD-C02	56,000 [16.4]	43,100 [12.6]	12,900 [3.8]	9.5	10.1	8.2	2000 [944]
	RCGA-60A1	55,500 [16.3]	40,900 [12.0]	14,600 [4.3]	9.4	10.0	8.2	2000 [944]
	RCHA-60A1	55,500 [16.3]	40,900 [12.0]	14,600 [4.3]	9.4	10.0	8.2	2000 [944]
	RCQB-C060	57,000 [16.7]	42,500 [12.5]	14,500 [4.2]	9.1	10.1	8.2	2000 [944]
	RBHC-24+RCBA-6089	57,500 [16.8]	41,300 [12.1]	16,200 [4.7]	9.2	10.0	8.2	1925 [908]
	RBHC-24+RCBA-6089+RXMD-C02	57,500 [16.8]	41,300 [12.1]	16,200 [4.7]	9.2	10.1	8.2	1925 [908]
	RBHC-24+RCGA-60A1	57,000 [16.7]	40,900 [12.0]	16,100 [4.7]	9.2	10.0	8.2	1925 [908]
	RBHC-24+RCHA-60A1	57,000 [16.7]	40,900 [12.0]	16,100 [4.7]	9.2	10.0	8.2	1925 [908]
	RBHC-26+RCBA-6089	57,000 [16.7]	40,900 [12.0]	16,100 [4.7]	9.1	10.0	8.2	1825 [861]
	RBHC-26+RCBA-6089+RXMD-C02	57,000 [16.7]	40,900 [12.0]	16,100 [4.7]	9.1	10.0	8.2	1825 [861]
	RBHC-26+RCGA-60A1	56,500 [16.6]	40,500 [11.9]	16,000 [4.7]	9.1	10.0	8.2	1825 [861]
	RBHC-26+RCHA-60A1	56,500 [16.6]	40,500 [11.9]	16,000 [4.7]	9.1	10.0	8.2	1825 [861]

① Highest sales volume tested combination required by D.O.E. test procedures.

## Electrical and Physical Data

Model Number RAKB-	ELECTRICAL							PHYSICAL					
	Phase Hertz Volts	Compr. (RLA)	Compr. (LRA)	Fan Motor (FLA)	Min. Circuit Ampacity Amperes	Fuse or HACR Circuit Breaker		Outdoor Coil			R22 Oz. [g]	Weight	
						Min. Amperes	Max. Amperes	Face Area Sq. Ft. [m²]	No. Rows	CFM [L/s]		Net Lbs. [kg]	Shipping Lbs. [kg]
018JA	1-60-208/230	9.6/9.6	47	0.9	13/13	20/20	20/20	5.9 [0.55]	1.00	1850 [874]	49 [1389]	130 [59.0]	140 [63.5]
024JA	1-60-208/230	11.9/11.9	59	0.9	16/16	20/20	25/25	5.9 [0.55]	1.00	1850 [874]	56 [1588]	135 [61.2]	145 [65.8]
030JA	1-60-208/230	14.1/14.1	69	0.9	19/19	25/25	30/30	9.0 [0.84]	1.00	1860 [877]	66 [1871]	145 [65.8]	155 [70.3]
036CA	3-60-208/230	10.3/10.3	77	1.3	15/15	20/20	20/20	11.0 [1.02]	1.00	2700 [1274]	79 [2240]	170 [77.1]	180 [81.6]
036DA	3-60-460	5.1	39	0.6	8/8	15	15	11.0 [1.02]	1.00	2700 [1274]	79 [2240]	170 [77.1]	180 [81.6]
036JA	1-60-208/230	16.5/16.5	95	1.3	22/22	30/30	35/35	11.0 [1.02]	1.00	2700 [1274]	79 [2240]	170 [77.1]	180 [81.6]
042CAS	3-60-208/230	11.6/11.6	73.4	1.3	16/16	20/20	25/25	11.0 [1.02]	1.00	2700 [1274]	79 [2240]	180 [81.6]	190 [86.2]
042CA	3-60-208/230	12.4/12.4	88	1.3	17/17	20/20	25/25	11.0 [1.02]	1.00	2700 [1274]	79 [2240]	180 [81.6]	190 [86.2]
042DAS	3-60-460	5.6	37	0.6	8	15	15	11.0 [1.02]	1.00	2700 [1274]	79 [2240]	180 [81.6]	190 [86.2]
042DA	3-60-460	6.4	44	0.6	9	15	15	11.0 [1.02]	1.00	2700 [1274]	79 [2240]	180 [81.6]	190 [86.2]
042JA	1-60-208/230	18.3/18.3	109	1.3	25/25	30/30	40/40	11.0 [1.02]	1.00	2700 [1274]	79 [2240]	180 [81.6]	190 [86.2]
048CAS	3-60-208/230	12.8/12.8	78	1.5	18/18	25/25	30/30	15.8 [1.47]	1.00	3500 [1652]	113 [3204]	200 [90.7]	210 [95.3]
048CA	3-60-208/230	12.8/12.8	91	1.5	18/18	25/25	30/30	15.8 [1.47]	1.00	3500 [1652]	103 [2920]	200 [90.7]	210 [95.3]
048DAS	3-60-460	6.9	41	1.0	10	15	15	15.8 [1.47]	1.00	3500 [1652]	113 [3204]	200 [90.7]	210 [95.3]
048DA	3-60-460	6.4	46	1.0	10	15	15	15.8 [1.47]	1.00	3500 [1652]	103 [2920]	200 [90.7]	210 [95.3]
048JA	1-60-208/230	21.8/21.8	131	1.5	29/29	35/35	50/50	15.8 [1.47]	1.00	3500 [1652]	103 [2920]	200 [90.7]	210 [95.3]
048YAS	3-60-575	5.1/5.1	36	0.7	8/8	15/15	15/15	15.8 [1.47]	1.00	3500 [1652]	113 [3204]	200 [90.7]	210 [95.3]
060CAS	3-60-208/230	16.7/16.7	110	1.5	23/23	30/30	35/35	15.8 [1.47]	1.00	3500 [1652]	112 [3175]	230 [104.3]	240 [108.9]
060CA	3-60-208/230	18.6/18.6	128	1.5	25/25	30/30	40/40	15.8 [1.47]	1.00	3500 [1652]	112 [3175]	230 [104.3]	240 [108.9]
060DAS	3-60-460	8.6	55	1.0	12	15	20	15.8 [1.47]	1.00	3500 [1652]	112 [3175]	230 [104.3]	240 [108.9]
060DA	3-60-460	9.0	63	1.0	13	15	20	15.8 [1.47]	1.00	3500 [1652]	112 [3175]	230 [104.3]	240 [108.9]
060JA	1-60-208/230	28.8/28.8	175	1.5	38/38	45/45	60/60	15.8 [1.47]	1.00	3500 [1652]	112 [3175]	230 [104.3]	240 [108.9]
060YAS	3-60-575	6.0	44	0.7	9	15	15	15.8 [1.47]	1.00	3500 [1652]	112 [3175]	230 [104.3]	240 [108.9]

[ ] Designates Metric Conversions