



























































XE 1000	MFR DATE 10/95
MOD. NO. TTR042C100A2	VOLTS 200/230
SERIAL NO. K413NHTBF	PH 1 HZ 60
MINIMUM CIRCUIT AMPACITY	30.0 AMPS
OVERCURRENT PROTECTIVE D	EVICE USA CANADA
RECOMMENDED FUSE / BREAKER (HACE	a) 50 50
MAX FUSE / BREAKER (HACR)	50 50
HCFC-22 6 LBS. 14 0Z	. OR 3,12 Kg(a)
BAYFCCY 080A REQUIRED INDOO	PRS FOR RATED PERFORMANCE
THE TRANE COMPANY TYLER, TX 75711-9010 MADE IN USA	OUTDOOR USE
COMPR. MOT. 23,0 RLA	200/230 V 119 LRA
O.D. MOT. 1.60 FLA M.E.A. NO. 56-92E	200/230 V 1/5 HP
DESIGN PSI - HIGH 300 LOW 300	F. ID. R19

MANUFACTU ONE OR MC FOLLOWING 4573,325 4593 4,720,981 4,723 4,720,981 4,723 4,720,981 4,723 4,972,935 0290

XE 1000			MFR DATE	10
MOD. NO. TTR042C100A2		V	OLTS I	200
SERIAL NO. K413NHTBF	PH	1	HZ	8
MINIMUM CIRCUIT AMPACITY			30.0	A
OVERCURRENT PROTECTIVE DE	VICE		USA	CA
RECOMMENDED FUSE / BREAKER (HACR)			50	
MAX FUSE / BREAKER (HACR)			50	7
HCFC-22 6 LBS. 14 0Z.	OR		3.12	Kg(
BAYFCCY 080A REQUIRED INDOORS	FORRA	TED	PERFO	RMA
THE TRANE COMPANY TYLER, TX 75711-9010 MADE IN USA	1		оштро	ORL
COMPR. MOT. 23.0 RLA	200/230		119	
O.D. MOT. 1.60 FLA 2	200/230	Y	1/5	
M.E.A. NO. 56-92E			~	

buildingcenter.org



























































































































































































